



BLADE SPECIFICATIONS

	Home-Pro 3000		Poly Sno-Pro		Sno-Pro 3000				Poly Trip-Edge		Trip-Edge Design			V-Plow		Commercial Garde	
Blade Length	7'	7 1/2'	7 1/2'	8'	7 1/2'	8'	8 1/2'	9'	7 1/2'	8'	7 1/2'	8'	9'	8'2"	9'2"	9' HD	10' HD
Blade Width (straight)	84"	90"	90"	96"	90"	96"	102"	108"	90"	96"	90"	96"	108"	98"	110"	108"	120"
Plowing Width (full angle)	74"	79.5"	79.5"	85"	74"	85"	90"	95"	79.5"	85"	79.5"	85"	95"	86 "	98"	95"	104 "
Blade Height	24"	28"	28"	28"	28*	28*	28"	28*	28"	28"	28*	28*	28*	28*	28"	33"	33*
Blade Skin Thickness	3/16**Poly	11 Ga	3/8" Poly	3/8" Poly	11 Ga	11 Ga	11 Ga	11 Ga	3/8" Poly	3/8" Poly	11 Ga	11 Ga	11 Ga	11 Ga	11 Ga	3/8" Poly	3/8* Poly
Cutting Edge	1" x6" Poly Reversible	3/4" x5" Polymer	3/8" x 6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	1/2" x 6" High Carbon Reversible	1/2" x6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	3/8" x6" High Carbon Reversible	3/8" x 6" High Carbon Reversible	1/2" x 6" High Carbon Reversible	1/2" x6" High Carbon Reversible	1/2" x6" High Carbon Reversible	5/8" x6" High Carbon Reversible	5/8" x6" High Carbon Reversible
Cutting Edge Attack Angle	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°	18°
Vertical Ribs	6	6	6	8	6	8	8	8	6	8	6	8	8	6	6	10	10
Trip Springs	2	4	4	4	4	4	4	4	4	4	4	4	4	4	4	6	6
Angle Cylinders	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"	2" x 10"DA	2" x 10"DA	2" x 12"	2" x 12"
Lift Cylinder	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 7.5"	1.5" x 10"	1.5" x 10"	2" x 10"	2" x 10"
Skid Shoes - Cast Iron	N/A	2	2	2	2	2	2	2	2	2	2	2	2	4	4	4	4
Sector	45*	54"	54"	54"	54*	54*	54"	54*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	62"	62*
Attachment System	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run	Hitch-N-Run
Jack System	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Switch Activated Hydraulic	Lever Activated Gas Lift	Lever Activated Gas Lift	Lever Activated Gas Lift	Lever Activated Gas Lift	Lever Activated Gas Lift	Spring Loaded Kick Stand	Spring Loaded Kick Stand	Spring Loaded Kick Stand	Spring Loaded Kick Stand
Average Weight	460 lbs.	690 lbs.	750 lbs.	795 lbs.	750 lbs.	795 lbs.	820 lbs.	850 lbs.	750 lbs	795 lbs.	750 lbs.	795 lbs.	850 lbs.	940 lbs.	970 lbs.	1100 lbs.	1175 lbs