

If you have any comments or concerns,  
please feel free to contact our  
customer service department at:  
Toll-free: 1-800-835-0438  
OR  
Email: info@gofia.com

SEAT COVERS  
BY



FEATURING  
SUPER-GRIP® THE SLIP RESISTANT FASTENING SYSTEM  
INSTALLATION INSTRUCTIONS  
FOR  
TR48-23, OE38-23, SP88-23

Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

**INSTRUCTIONS:**

**A) BACKREST COVER – BUCKETS / “40” PORTION X 2:**

- 1) Remove head rest (see note)
- 2) Slip cover over backrest
- 3) Tuck flaps under backrest and attach to Velcro at back
- 4) Adjust Velcro to equalize tension
- 5) Replace headrests (see note)

**B) CUSHION COVER - BUCKETS / “40” PORTION X 2:**

- 1) Center cover on the seat
- 2) Pass the front strap under seat. Buckle to back flap
- 3) Pass side straps through the opening between the molded plastic and the seat. Buckle to back flap
- 4) Adjust straps and buckles to equalize tension

**C) BACKREST COVER – “20” PORTION:**


- 1) Slip cover over armrest so armrest is covered when in up position. (top of armrest in down position is not covered).
- 2) Snug cover at back of armrest so the velcro on cover is positioned through the crevice where lid and armrest are hinged
- 3) Open armrest/console lid and position adhesive back velcro (supplied) to align with velcro on cover
- 4) Snug cover at front of armrest and position adhesive back velcro tabs (supplied) to the inside well of cup holder
- 5) Snug both sides of the cover and position adhesive back velcro (supplied) inside armrest/console
- 6) Secure all velcros

**D) CUSHION/COMPARTMENT COVER– “20” PORTION:**

- 1) Open lid
- 2) Slip cover over lid, pull down firmly and velcro at bottom of cover

**NOTES:**

**1) SELF-LOCKING SUPER-GRIP® BUCKLE:**



**3) RE-INSTALLATION OF HEADRESTS**

- A) Ensure pre-cut holes in seat cover align with holes in headrest base.
- B) Replace headrests


**2) HEAD REST REMOVAL:**

- A) - Insert paper clip into holes at base to release
- Lift off

**OR**

- B) - Push in side release buttons
- Lift off

(If unable to remove consult dealership)



**WARNING: NEVER INSTALL SEAT COVERS ON SEATS WITH BUILT-IN AIRBAGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS WHICH COULD RESULT IN SERIOUS INJURY.**



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438  
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com